

GTB4R //X

Gasoline System Test Bench



The Optimum Gasoline Specialists GDi Solution

The Professional's Service Station for All Types and Makes GDI systems.





GTB4R //X



// 1200 Bar

4 GDi injectors. Capable for all EU6 technologies

A Revolution in GDi Test Benches

Our qualified team, know-how and pioneering thinking developed the New Powerful **GTB.4R|X**



GTB4R //X

an OE Approved Solution

The New GTB.4R|X is a unique Standalone Gasoline Injector Testbench capable to thoroughly Test, Service and code every possible GDi in the Market today.

The machine's Innovative technology is already in compliance with all EU6 Standards and requirements, meantime is prepared for future upgrades.

#carbonzappXseries



///// Evaluation of the New GTB.4R|X

5-7 minutes testing time for:


4 GDi injectors (All Brands and Types). Capable for all EU6 technologies

Precise, repeatable and rapid Gasoline Injectors Testing

Coding Capable for all Types of GDi's (Energy Controlled or Volume Metering types)

Flushing and Servicing options for GDi injectors





GDi Pump testing on a conventional bench as an external control & measurement*

Applications

Gasoline Passenger cars

Gasoline Light Duty vehicles

Gasoline Outboard motors

Alternative Fuels engines

Features

Xtremely Fast Testing Times without any Compromise

New Design for every Service Station

Optimized Working Area to reduce Injector Set-up Times

1200Bar Capable Test Bench

EU6 Systems Testing and Coding

CloudX Capabilities

CloudX

Cloud Based Technology

Industry 4.0 Complaint

Remote Sync & Backup

Machine Fleet Management

Online Features Activation


Instant Troubleshooting & Support

AZO Software v3.0

Powered by CloudX







DGS (III)

Diesel & Gasoline Spesialists Solutions

Ergonomic, Fast and Easy Injector Clamping device to minimize mounting times.

Fully Adjustable height for all types of CR injectors.

Utilizes a spring-loaded injector holder to ease the operation of the user.

Quick access to all inline filters for fast check-up and replacement located within your working area. A mess-free compartment to work at, continuously draining to the waste tank.

Advanced Testing capability for all brands and types available in the market today. Bosch, Denso, Delphi, Continental /VDO, Hitachi-HTC, Magneti Marelli and more added every day...

Coding capability for Siemens/ VDO and for the newer* generation EU6 available in the market today.

Advanced water-cooling or air-cooling system to optimize long term nonstop operation at all environmental conditions.

Live Response Time Measurement at every test plan

Adaptability for every type of Gasoline Injectors in the market

Continuous Database updates and new Software capabilities to meet the market needs.

Android Powered 15.6' HMI with unlimited flexibility and connectivity competencies.

GTB4R //X Technical Data

	Part Number	GTB.4RX
	Standalone Add-On Cooling Type	- [A/W]
ТҮРЕ	Test Bench Simulator / Controller Cambox Service / Diagnostic Unit	• - -
USER LEVEL	Diesel / Gasoline Specialists Workshop / Garage Test Slots [injectors / Pumps]	• o [4/1]
SYSTEMS / [TESTING MINUTES]	CRDi / Smart Injectors [1 / 4] GDi Injectors [1 / 4] CR Pumps [1] GDi Pumps [1] EUI / EUP / Smart EUP [1] HEUI [1 / 4] Gasoline Injectors [1 / 4] LPG / CNG Injectors [1 / 4] Gasoline / Other Engines Diesel Engines Gasoline / Diesel Fuel Systems	•/[-/6] - -/[5] - - - - - -
APPLICATIONS	Passenger Car / HEV / PHEV Motorcycles Racing (Gasoline) Light Duty Medium Duty Heavy Duty / Industrial Marine EV (Electric Vehicles)	• • • • - -
FEATURES	Coding Capability for Passenger Car / Light Duty Coding Capability for Medium/Heavy Duty Authorized Solutions	- -
MEASUREMENT SENSORS	XKM DFM500 DFM50 Volumetric Tubes	4 - - -
SYSTEM PRESSURE	Max (BAR) Source Source Power (HP)	1200 MOTOR 4,8
CHARACTERISTICS	Response Sensor Response Sensor HD Pressurized Return Hoses / PIRV's Exclusive Return Hoses Kit Spray Chamber Heavy Duty Injector Adapters & Fittings Heavy Duty Pump Adapters & Fittings Exclusive Electrical Connectors Mains Power 50/60Hz /1-Phase 100-250VAC Mains Power 50/60Hz /3-Phase/PE 380-480VAC Air-Supply (Bar / L/min) Water Cooling (requires connection) Air Cooling Tank Capacity [testing / flushing] HMI (Inches) Touchscreen Flushing / MACC Protective Cover Calibration Oils Ultrasonic Bath	
PACKAGING	Width (mm) Depth (mm) Height (mm) Weight (kg)	920 1160 1870 352

MEASUREMENT SENSORS
XKMI Dynamic Meas. Sensorj: High Accuracy; ± 0,1%, Exceptional Repeatability ±0,05%,
Measur, Range: 1-1000ml/min
DFM SOOI Dynamic Measurement Sensorj: Accuracy; ± 1%, Repeatability 0,5%, Measurement range: 5-500lt/min
DFM SOID/pynamic Measurement Sensorj: Accuracy; ± 1%, Repeatability 0,5%, Measurement range: 0,5-50lt/min
Volumetri Tubes (Static Andiag Measurement): Accuracy; rIII, Measurement range: 0,5-50lt/min

APPLICATIONS
Passenger Car/ Motorcycles: Volumes up to 120mm3/H
Light Duty: Volumes up to 200mm3/H
Medium Duty, Volumes up to 500mm3/H
Heavy Duty: Volumes up to 650mm3/H
Marines, Volumes up to 1500mm3/H

EXPLANATIONS

Capable / Standard Equipped

Capable / Optional's required

Notional

ANA

NA

NA

NA

NA

NA

NA

An Air Doubre High Pressure CR Pump

And Air Otto Driven High Pressure CR Pump

State Capable

Electrical Pump: Leel Injection system or Industrial Application

H

Electrical Pump: Leel Injection system or Industrial Application

H

Electrical Pump: Leel Injection System or Industrial Application

H

Electrical Pump: Source

N

Electrical Pump: Source

Electrical Pump: Source

N

Electrical Pump: Source

Electrical Pump: Source

N

Electrical Pump: Source

N

Electrical Pump: Source

Electrical Pump: Source

N

Electrical Pump: Source

N

Electrical Pump: Source

Elect